

## QSAN Flash Storage

**XCubeFAS 3126**

Liberate Enterprise Applications, Enter the Modern Data Era

**Key Benefits****Excellent Performance**

- 100% NVMe 3U26 high density architecture
- Flexible high-speed 25 GbE iSCSI / 32 Gb Fibre Channel I/O host card
- Excellent IOPS with ultra-low latency  
450K random write IOPS @ 500µs latency, 220K random write IOPS @ 300µs latency

**Enterprise-grade Reliability**

- 99.9999% high availability design with no single point of failure
- Never lose any data at cache-to-flash memory protection solution
- Always enjoy the latest features & better performance with zero downtime firmware upgrade

**Modern Simplicity**

- Simplify the steps of upgrading and replacing system components with modular hardware design
- XEVO - the operation system for flash storage reduces learning and maintenance efforts through our innovative interface design
- Support RESTful API, SNMP, and emailing for external management or use QSAN XInsight, smarter data management with simplified platform and intelligent engine

**The Best NVMe Flash Storage in Businesses of All Sizes**

QSAN XF3126, the world's first and the fastest entry-level NVMe flash storage. XF3126 provides high performance with µs-level latency that can meet the response requirements of the most demanding enterprise applications. It is the perfect modern IT solution for database, AI, IOT, HPC, virtualization, and financial services.

**Accelerate Business-Critical Applications**

QSAN XF3126 with 26-bay NVMe architecture guarantees steady response time rather than one-time peak throughput, and achieves the requirements of the enterprise highperformance computing infrastructures with high IOPS at µs-level latency. At low latency, there's no need to be worried about applications that slow down, or worse, stop running due to high response time, and you can speed up the computing process by reducing the data transmission time and integrate mixed critical workloads in flash storage.


**Business Continuity**

The cost of losing confidence from customers is far greater than the cost of IT recovery. XF3126 has a built-in hot-swappable and fully redundant hardware design for easy maintenance and upgrade. Dual active controllers concurrently provide storage services in real-time and guarantee the non-stop storage service.

**Efficiency Management**

The flash-based storage management system - XEVO, providing efficiency management capabilities, data can be accessed in just 5 minutes when storage is installed for the first time. With the help of comprehensive and intuitive dashboard and report system, managers are able to analyze business usage and monitor the storage status in real time. Moreover, external manage features such as RESTful API, SNMP and emailing notification enable managers to fully grasp the system status and focus on better decision making.

## Appearance



1. Enclosure Power Button / LED
2. UID (Unique Identifier) Button / LED
3. Enclosure Access LED
4. Enclosure Status LED
5. USB Port
6. Disk Drive Power LED
7. Disk Drive Status LED
8. PSU Indicator
9. Controller Status LED
10. Master / Slave LED (only for dual controllers)
11. Dirty Cache LED
12. UID (Unique Identifier) LED
13. Host Card Slot 1 (host card is an optional part)
14. Host Card Slot 2 (host card is an optional part)
15. Buzzer Mute Button
16. Reset to Factory Default Button
17. Management Port
18. Console Port
19. Service Port
20. USB Port
21. 10 GbE iSCSI SPF+ Port

## System Specification

Model Name	XF3126D	XF3126S
Architecture	Dual-active controller	Single-upgradeable controller
CPU		
Processor	Intel® Xeon® 64-bit 6-core	
Memory		
Memory Module Pre-installed	16 GB DDR4 RDIMM (per controller)	
Total Memory Slots	6 (per controller)	
Memory Expandable up to	384 GB (per controller)	
Storage		
Drive Bays	2.5" Slot x 26	
Maximum Drive Bays with Expansion Unit	26	
Compatible Drive Type	2.5" dual-port U.2 NVMe SSD	2.5" single-port U.2 NVMe SSD
Drive Interface	U.2 NVMe (PCIe Gen 4x4)	
Maximum Internal Raw Capacity	399 TB (calculate 15.36 TB SSD)	
Hot Swappable Drive	Yes	
Connectivity Port		
PCIe Expansion	(Gen 3x8 Slot) x 2	
1 GbE RJ45 LAN Port	1 (onboard management port per controller)	
10 GbE SFP+ LAN Port	2 (onboard per controller) / 4 (option)	
10 GbE RJ45 LAN Port	2 (option) / 4 (option)	
25 GbE SFP28 LAN Port	2 (option) / 4 (option)	
16 Gb SFP+ Fibre Channel	2 (option) / 4 (option)	
32 Gb SFP28 Fibre Channel	2 (option)	
Expansion and External Port		
USB Port	1 (front) / 1 (rear)	
Others	Console Port x 1, Service Port (UPS) x 1	
Software Specification		
Storage OS	XEVO	
RAID Type	0 / 1 / 3 / 5 / 6 / 10 / 30 / 50 / 60 / 5EE / 6EE / 50EE / 60EE / N-way mirror	
Storage Efficiency	Thin provisioning	
Data Protection	Snapshot / Local volume clone	
Remote Replication	Asynchronous (built-in) / Synchronous (option)	
Security	HTTPS / SSH / iSCSI CHAP / ISE & SED	
Management	Web UI / Serial console / RESTful API / S.E.S. / LCM	
Others		
Memory Protection	Cache-to-Flash (built-in)	
System Fan	4 pcs (per controller)	
Certification	CE / FCC / BSMI	
Standard Warranty	System: 3 years Cache-to-Flash Module: 1 year	