

Data Sheet



QSAN Unified Storage

XCubeNXT 5124

Value-Optimized Unified Storage for SMB

Key Benefits

Modern Simplicity

- QSM storage management system minimizes the learning curve and eases maintenance through an intuitive GUI
- Fast setup and data can be accessed in 5 minutes after installation
- Multiple protocol support and cross QSAN platform replication

Dependable Data Experience

- 99.9999% high availability design with no single point of failure
- Cache-to-flash to protect cache data in power outage
- Non-disruptive firmware upgrade ensures continuous data service with zero downtime

Flexible Expansion

- Dual controller with built-in 4-port 10 GbE (SFP+) and maximum 26 host ports allows direct connection to multiple hosts without switches
- Outstanding scale-up capability up to 11 PB
- Wake-on-SAS allows you to remotely power on / off all cascaded XCubeDAS expansion units for power saving

Best TCO for Capacity-Demanding Applications

The XCubeNXT 5124 (3.5" 4U 24-bay) is the newest generation of XCubeNXT that wields the best TCO for capacity-demanding applications. Highly available and secure with multiple protocol and cross QSAN platform support, it is designed to be ideal for modern enterprise applications such as virtualization, containerization, surveillance, and backup. Plus, backed by a 5-year limited warranty for proven enterprise-grade reliability.

Proven Simplicity - "Set and Forget" Data Services

QSM, a storage management system with intuitive GUI designs, helps to save time in storage deployment considerably. It also delivers unified storage features including support for a range of multi protocols (CIFS, NFS, FTP*, iSCSI, FCP*, etc.), complete RAID level protection, RAID EE, thin provisioning, SSD cache, auto-tiering, compression, inline deduplication, and more. With the help of an intuitive dashboard, managers can monitor storage status in real time.

Advanced Data Protection to Safeguard Assets

Built-in various backup methods such as snapshot, remote replication, rsync, cloud backup*, etc. to help you complete data backup and data integrity. In addition, a big leap forward, it can replicate to all QSAN storage platform to thoroughly protect your assets.

Secure Data and Secure Management

QSM continuously evolves our security level to protect data across storage and adhere to industry best practices. Supporting SED (Self-Encrypting Drives) coupled with WORM* will keep your sensitive data safe even if the drives are lost, stolen, or misplaced. Additionally, Windows ACL (Access Control List) and RBAC (Role-Based Access Control) helps to prevent unauthorized access to your data.

High Availability and Enterprise Reliability


The XCubeNXT series is a proven high availability unified storage system with full redundancy. Its dual-active architecture and cache-to-flash technology ensure optimal performance and resilience in critical situations.

Flexible I/O Modules and Scale-up Capacity as Needed

Each controller has two host card slots that can be configured as iSCSI, Fibre Channel, or a mix of both besides built-in 4-port 10 GbE iSCSI (SFP+). As a result, the series offers great flexibility with built-in 8-port 10 GbE iSCSI (SFP+) and up to 26 host ports in a dual-controller system. In addition, the XN5124 provides massive scale-up capabilities by connecting XCubeDAS or 3rd-party expansion units with up to 504 disk drives or 11 PB raw capacity for future data growth.

* The feature will be available in Q1, 2024.

Appearance



1. Enclosure Status LED
2. Enclosure Access LED
3. Enclosure Power Button / LED
4. Disk Drive Status LED
5. Disk Drive Power LED
6. USB Port
7. UID (Unique Identifier) Button / LED
8. Power Supply Unit
9. Master / Slave LED (only for dual controllers)
10. Controller Status LED
11. Dirty Cache LED
12. UID (Unique Identifier) LED
13. 12 Gb/s SAS Wide Port
14. 10 GbE LAN Port
15. 1 GbE LAN Port
16. Host Card Slot 1 (host card is an optional part)
17. Service Port
18. Console Port
19. USB Port
20. Host Card Slot 2 (host card is an optional part)
21. Reset to Factory Default Button
22. Buzzer Mute Button

System Specification

| Model Name | XN5124D | XN5124S |
|---|---|---|
| Architecture | Dual-active controller | Single-upgradeable controller |
| CPU | Intel® Xeon® 64-bit 4-core | |
| Memory | 8 GB DDR4 ECC DIMM (per controller) | |
| Memory Module Pre-installed | 8 GB DDR4 ECC DIMM (per controller) | |
| Total Memory Slots | 4 (per controller) | |
| Memory Expandable up to | 256 GB (per controller) | |
| Storage | 3.5" Slot x 24 | |
| Drive Bays | 3.5" Slot x 24 | |
| Maximum Drive Bays with Expansion Unit | 504 | |
| Compatible Drive Type | 3.5" & 2.5" SAS, NL-SAS, SED HDD 2.5" SAS, SED SSD | 3.5" & 2.5" SAS, NL-SAS, SED HDD 3.5" & 2.5" SATA(*) HDD 2.5" SAS, SATA(*), SED SSD |
| Drive Interface | SAS 12 Gb/s | SAS 12 Gb/s, SATA 6 Gb/s(*) (*) SATA drives only work with single controller systems |
| Maximum Internal Raw Capacity | 528 TB (calculate 22 TB HDD) | |
| Maximum Raw Capacity with Expansion Units | 11,088 TB (calculate 22 TB HDD) | |
| Hot Swappable Drive | Yes | |
| Connectivity Port | PCIe Expansion (Gen 3x8 Slot) x 2 1 GbE RJ45 LAN Port 1 (onboard per controller) 10 GbE SFP+ LAN Port 4 (onboard per controller) / 4 (option) 10 GbE RJ45 LAN Port 4 (option) 25 GbE SFP28 LAN Port 2 (option) / 4 (option) 16 Gb SFP+ Fibre Channel* 2 (option) / 4 (option) 32 Gb SFP28 Fibre Channel* 2 (option) | |
| Expansion and External Port | 12 Gb/s SAS Wide Port 2 (onboard per controller) USB Port 1 (front) / 2 (rear) Others Console Port x 1, Service Port (UPS) x 1 | |
| Software Specification | Storage OS QSM 4 RAID Type 0 / 1 / 3 / 5 / 6 / 10 / 30 / 50 / 60 / 5EE / 6EE / 50EE / 60EE Storage Efficiency Thin provisioning / Deduplication (option) / Compression (option) Software Acceleration SSD cache / Auto tiering Data Protection Snapshot / Asynchronous / Synchronous (option) Backup Services Rsync / S3 backup / Cloud sync* / XMirror* Security SSL / SED / WORM* / RBAC / Windows ACL Support Protocols CIFS / NFS / FTP* / AFP* / iSCSI / FCP* Management Web UI / Window AD / LDAP / RESTful API* / S.E.S. / LCM | |
| Appearance | Dimension (H x W x D) (mm) 170.3 x 438 x 515 Net Weight (kg) 25.9 Gross Weight (kg) 28.3 | |
| Others | Memory Protection Cache-to-Flash (Supercapacitor Module + Flash Module) (option) System Fan 4 pcs Power Supply Unit 850 W x 2 (80 PLUS Platinum) Power Consumption 648 W Certification CE / FCC / BSMI Standard Warranty System: 5 years Supercapacitor Module: 1 year | |

* The feature will be available in Q1, 2024.

© Copyright 2023 QSAN Technology, Inc. All Rights Reserved. XCubeFAS, XCubeNXT, XCubeNAS, XCubeSAN and XCubeDAS are trademarks of QSAN Technology, Inc. All other trademarks are the property of their respective owners. Product features, specifications, and appearance are subject to change without notice.

