

Data Sheet

QSAN Hybrid Flash Storage

XCubeSAN 3300

Optimizing Price and Performance for SMB Workloads

Key Benefits

Outstanding Performance

- Industry leading density with dual active architecture
- Excellent performance with 12.8 GB/s and 1.3M IOPS
- Outstanding scale-up capability up to 16.7 PB

Dependable Data Experience

- 99.9999% high availability design with no single point of failure
- Cache-to-flash to protect cache data in power outage
- Non-disruptive firmware upgrade ensures continuous data service with zero downtime

Versatile Connectivity

- Each controller with built-in 4-port 10 GbE and maximum 12 host ports allows direct connection to multiple hosts without switches
- Optional high-speed 25 GbE iSCSI and 32 Gb Fibre Channel host cards

Modern Simplicity

- XEVO, a flash-based storage management system, minimizes the learning curve and eases maintenance through an intuitive GUI
- Data can be accessed in 5 minutes after installation
- Wake-on-SAS allows you to remotely power on / off all cascaded XCubeDAS expansion units for power saving

Leading Density with Uncompromised Performance

The XCubeSAN 3300 series is an affordable hybrid flash storage system. The new standard for entry-level storage workloads with extreme simplicity, scalability, and a balance of performance and price for SMB limited budgets. Offers outstanding performance ideal for modern applications such as virtualization, media editing, large scale surveillance, and backup.

High Availability and Enterprise Reliability

The XCubeSAN series is a proven high availability SAN storage system with full redundancy in modular design. Its dual-active architecture and automatic failover / failback mechanism, coupled with cache-to-flash technology, enables the system to withstand critical situations.

Flexible I/O Modules and Scale-up Capacity as Needed

Each controller has two host card slots that can be configured as iSCSI, Fibre Channel, or a mix of both besides built-in 4-port 10 GbE iSCSI. As a result, the series offers great flexibility with built-in 8-port 10 GbE iSCSI and up to 24 host ports in a dual-controller system. In addition, the XS3326 provides massive scale-up capabilities by connecting XCubeDAS or 3rd-party expansion units with up to 546 disk drives or 16.7 PB raw capacity for future data growth.

Proven Simplicity - "Set and Forget" Data Services

XEVO, a storage management system with intuitive GUI designs, helps to save time in storage deployment considerably. XEVO also delivers enterprise storage features including complete RAID level protection, RAID EE with fast rebuild, thin provisioning, SSD cache, auto-tiering, and more. With the help of an intuitive dashboard and reporting system, managers can analyze business usage and monitor storage status in real time.

Advanced Data Protection to Safeguard Assets

To protect against data loss and downtime events, XEVO provides complete array-based backup functions including local backup and remote replication. Based on snapshot technology, a solid safety net for disaster recovery can be built to meet the required RPO and RTO.


Secure Data and Secure Management

Supporting SED (Self-Encrypting Drives) will keep your sensitive data safe even if the drives are lost, stolen, or misplaced. Additionally, RBAC (Role-Based Access Control) helps to prevent unauthorized access to your data. All management communication is secured over https.

QSAN

Appearance





1. Enclosure Status LED
2. Enclosure Access LED
3. Enclosure Power Button / LED
4. Disk Drive Status LED
5. Disk Drive Power LED
6. USB Port
7. UID (Unique Identifier) Button / LED
8. Power Supply Unit
9. Master / Slave LED (only for dual controllers)
10. Controller Status LED
11. Dirty Cache LED
12. UID (Unique Identifier) LED
13. 12 Gb/s SAS Wide Port
14. 10 GbE LAN Port
15. 1 GbE LAN Port (management port)
16. Host Card Slot 1 (host card is an optional part)
17. Service Port
18. Console Port
19. USB Port
20. Host Card Slot 2 (host card is an optional part)
21. Reset to Factory Default Button
22. Buzzer Mute Button


System Specification

Model Name	XS3326D	XS3326S
Architecture	Dual-active controller	Single-upgradable controller
CPU		
Processor	Intel® Xeon® 4-core x 2	Intel® Xeon® 4-core
Memory		
Memory Module Pre-installed	16 GB DDR4 RDIMM	8 GB DDR4 RDIMM
Total Memory Slots	8	4
Memory Expandable up to	512 GB	256 GB
Storage		
Drive Bays	2.5" Slot x 26	
Maximum Drive Bays with Expansion Unit	546	
Compatible Drive Type	2.5" SAS, NL-SAS, SED HDD 2.5" SAS, SED SSD	2.5" SAS, NL-SAS, SED HDD 2.5" SATA HDD 2.5" SAS, SATA, SED SSD
Drive Interface	SAS 12 Gb/s	SAS 12 Gb/s, SATA 6 Gb/s
Maximum Internal Raw Capacity	798 TB	
Maximum Raw Capacity with Expansion	16,773 TB	
Hot Swappable Drive	Yes	
Connectivity Port		
PCIe Expansion	(Gen 3x8 Slot) x 4	(Gen 3x8 Slot) x 2
1 GbE RJ45 LAN Port	2 (onboard)	1 (onboard)
10 GbE SFP+ LAN Port	8 (onboard) / 4 (option)	4 (onboard) / 4 (option)
10 GbE RJ45 LAN Port	2 (option) / 4 (option)	
25 GbE SFP28 LAN Port	2 (option) / 4 (option)	
16 Gb SFP+ Fibre Channel	2 (option) / 4 (option)	
32 Gb SFP28 Fibre Channel	2 (option) / 4 (option)	
Expansion and External Port		
12 Gb/s SAS Wide Port	4 (onboard)	2 (onboard)
USB Port	1 (front) / 2 (rear)	1 (front) / 1 (rear)
Others	Console Port x 2, Service Port x 2	Console Port x 1, Service Port x 1
Software Specification		
Storage OS	XEVO 2	
RAID Type	0 / 1 / 3 / 5 / 6 / 10 / 30 / 50 / 60 / 5EE / 6EE / 50EE / 60EE	
Storage Efficiency	Thin provisioning	
Software Acceleration	SSD cache (option) / Auto tiering (option)	
Data Protection	Snapshot / Asynchronous / Synchronous (option)	
Security	SSL / SSH / iSCSI CHAP / ISE & SED	
Support Protocols	iSCSI / FCP	
Management	Web UI / RESTful API / S.E.S. / LCM	
Appearance		
Dimension (H x W x D) (mm)	88 x 438 x 491	
Net Weight (kg)	16.3	
Gross Weight (kg)	18.6	
Others		
Memory Protection	Cache-to-Flash Module (Supercapacitor Module + Flash Module) (option)	
System Fan	4 pcs	
Power Supply Unit	850 W x 2 (80 Plus Platinum)	
Power Input	100 - 240 VAC, 50/60 Hz	
Power Consumption	429 W / 1,464 BTU	
Certification	CE / FCC / BSMI	
Standard Warranty	System: 3 years Supercapacitor Module: 1 year	

© 2025 QSAN Technology, Inc. All Rights Reserved. QSAN and the QSAN logo are registered trademarks of QSAN Technology, Inc. Other trademarks are the property of their respective companies. Product features, specifications, and appearance are subject to change without notice.

August 2025

Appearance



1. Enclosure Status LED
2. Enclosure Access LED
3. Enclosure Power Button / LED
4. Disk Drive Status LED
5. Disk Drive Power LED
6. USB Port
7. UID (Unique Identifier) Button / LED
8. Power Supply Unit
9. Master / Slave LED (only for dual controllers)
10. Controller Status LED
11. Dirty Cache LED
12. UID (Unique Identifier) LED
13. 12 Gb/s SAS Wide Port
14. 10 GbE LAN Port
15. 1 GbE LAN Port (management port)
16. Host Card Slot 1 (host card is an optional part)
17. Service Port
18. Console Port
19. USB Port
20. Host Card Slot 2 (host card is an optional part)
21. Reset to Factory Default Button
22. Buzzer Mute Button


System Specification

Model Name	XS3324D	XS3324S
Architecture	Dual-active controller	Single-upgradable controller
CPU		
Processor	Intel® Xeon® 4-core x 2	Intel® Xeon® 4-core
Memory		
Memory Module Pre-installed	16 GB DDR4 RDIMM	8 GB DDR4 RDIMM
Total Memory Slots	8	4
Memory Expandable up to	512 GB	256 GB
Storage		
Drive Bays	3.5" Slot x 24	
Maximum Drive Bays with Expansion Unit	504	
Compatible Drive Type	3.5" & 2.5" SAS, NL-SAS, SED HDD 2.5" SAS, SED SSD	3.5" & 2.5" SAS, NL-SAS, SED HDD 3.5" & 2.5" SATA HDD 2.5" SAS, SATA, SED SSD
Drive Interface	SAS 12 Gb/s	SAS 12 Gb/s, SATA 6 Gb/s
Maximum Internal Raw Capacity	624 TB	
Maximum Raw Capacity with Expansion	13,104 TB	
Hot Swappable Drive	Yes	
Connectivity Port		
PCIe Expansion	(Gen 3x8 Slot) x 4	(Gen 3x8 Slot) x 2
1 GbE RJ45 LAN Port	2 (onboard)	1 (onboard)
10 GbE SFP+ LAN Port	8 (onboard) / 4 (option)	4 (onboard) / 4 (option)
10 GbE RJ45 LAN Port	2 (option) / 4 (option)	
25 GbE SFP28 LAN Port	2 (option) / 4 (option)	
16 Gb SFP+ Fibre Channel	2 (option) / 4 (option)	
32 Gb SFP28 Fibre Channel	2 (option) / 4 (option)	
Expansion and External Port		
12 Gb/s SAS Wide Port	4 (onboard)	2 (onboard)
USB Port	1 (front) / 2 (rear)	1 (front) / 1 (rear)
Others	Console Port x 2, Service Port x 2	Console Port x 1, Service Port x 1
Software Specification		
Storage OS	XEVO 2	
RAID Type	0 / 1 / 3 / 5 / 6 / 10 / 30 / 50 / 60 / 5EE / 6EE / 50EE / 60EE	
Storage Efficiency	Thin provisioning	
Software Acceleration	SSD cache (option) / Auto tiering (option)	
Data Protection	Snapshot / Asynchronous / Synchronous (option)	
Security	SSL / SSH / iSCSI CHAP / ISE & SED	
Support Protocols	iSCSI / FCP	
Management	Web UI / RESTful API / S.E.S. / LCM	
Appearance		
Dimension (H x W x D) (mm)	170.3 x 438 x 515	
Net Weight (kg)	25.9	
Gross Weight (kg)	28.3	
Others		
Memory Protection	Cache-to-Flash Module (Supercapacitor Module + Flash Module) (option)	
System Fan	4 pcs	
Power Supply Unit	850 W x 2 (80 Plus Platinum)	
Power Input	100 - 240 VAC, 50/60 Hz	
Power Consumption	648 W / 2,211 BTU	
Certification	CE / FCC / BSMI	
Standard Warranty	System: 3 years Supercapacitor Module: 1 year	

© 2025 QSAN Technology, Inc. All Rights Reserved. QSAN and the QSAN logo are registered trademarks of QSAN Technology, Inc. Other trademarks are the property of their respective companies. Product features, specifications, and appearance are subject to change without notice.

Appearance





1. Enclosure Status LED
2. Enclosure Access LED
3. Enclosure Power Button / LED
4. Disk Drive Status LED
5. Disk Drive Power LED
6. USB Port
7. UID (Unique Identifier) Button / LED
8. Power Supply Unit
9. Master / Slave LED (only for dual controllers)
10. Controller Status LED
11. Dirty Cache LED
12. UID (Unique Identifier) LED
13. 12 Gb/s SAS Wide Port
14. 10 GbE LAN Port
15. 1 GbE LAN Port (management port)
16. Host Card Slot 1 (host card is an optional part)
17. Service Port
18. Console Port
19. USB Port
20. Host Card Slot 2 (host card is an optional part)
21. Reset to Factory Default Button
22. Buzzer Mute Button

System Specification


Model Name	XS3316D	XS3316S
Architecture	Dual-active controller	Single-upgradable controller
CPU		
Processor	Intel® Xeon® 4-core x 2	Intel® Xeon® 4-core
Memory		
Memory Module Pre-installed	16 GB DDR4 RDIMM	8 GB DDR4 RDIMM
Total Memory Slots	8	4
Memory Expandable up to	512 GB	256 GB
Storage		
Drive Bays	3.5" Slot x 16	
Maximum Drive Bays with Expansion Unit	496	
Compatible Drive Type	3.5" & 2.5" SAS, NL-SAS, SED HDD 2.5" SAS, SED SSD	3.5" & 2.5" SAS, NL-SAS, SED HDD 3.5" & 2.5" SATA HDD 2.5" SAS, SATA, SED SSD
Drive Interface	SAS 12 Gb/s	SAS 12 Gb/s, SATA 6 Gb/s
Maximum Internal Raw Capacity	416 TB	
Maximum Raw Capacity with Expansion	12,896 TB	
Hot Swappable Drive	Yes	
Connectivity Port		
PCIe Expansion	(Gen 3x8 Slot) x 4	(Gen 3x8 Slot) x 2
1 GbE RJ45 LAN Port	2 (onboard)	1 (onboard)
10 GbE SFP+ LAN Port	8 (onboard) / 4 (option)	4 (onboard) / 4 (option)
10 GbE RJ45 LAN Port	2 (option) / 4 (option)	
25 GbE SFP28 LAN Port	2 (option) / 4 (option)	
16 Gb SFP+ Fibre Channel	2 (option) / 4 (option)	
32 Gb SFP28 Fibre Channel	2 (option) / 4 (option)	
Expansion and External Port		
12 Gb/s SAS Wide Port	4 (onboard)	2 (onboard)
USB Port	1 (front) / 2 (rear)	1 (front) / 1 (rear)
Others	Console Port x 2, Service Port x 2	Console Port x 1, Service Port x 1
Software Specification		
Storage OS	XEVO 2	
RAID Type	0 / 1 / 3 / 5 / 6 / 10 / 30 / 50 / 60 / 5EE / 6EE / 50EE / 60EE	
Storage Efficiency	Thin provisioning	
Software Acceleration	SSD cache (option) / Auto tiering (option)	
Data Protection	Snapshot / Asynchronous / Synchronous (option)	
Security	SSL / SSH / iSCSI CHAP / ISE & SED	
Support Protocols	iSCSI / FCP	
Management	Web UI / RESTful API / S.E.S. / LCM	
Appearance		
Dimension (H x W x D) (mm)	130.4 x 438 x 515	
Net Weight (kg)	21.7	
Gross Weight (kg)	24	
Others		
Memory Protection	Cache-to-Flash Module (Supercapacitor Module + Flash Module) (option)	
System Fan	4 pcs	
Power Supply Unit	850 W x 2 (80 Plus Platinum)	
Power Input	100 - 240 VAC, 50/60 Hz	
Power Consumption	534 W / 1,822 BTU	
Certification	CE / FCC / BSMI	
Standard Warranty	System: 3 years Supercapacitor Module: 1 year	

© 2025 QSAN Technology, Inc. All Rights Reserved. QSAN and the QSAN logo are registered trademarks of QSAN Technology, Inc. Other trademarks are the property of their respective companies. Product features, specifications, and appearance are subject to change without notice.

August 2025

Appearance





1. Enclosure Status LED
2. Enclosure Access LED
3. Enclosure Power Button / LED
4. Disk Drive Status LED
5. Disk Drive Power LED
6. USB Port
7. UID (Unique Identifier) Button / LED
8. Power Supply Unit
9. Master / Slave LED (only for dual controllers)
10. Controller Status LED
11. Dirty Cache LED
12. UID (Unique Identifier) LED
13. 12 Gb/s SAS Wide Port
14. 10 GbE LAN Port
15. 1 GbE LAN Port (management port)
16. Host Card Slot 1 (host card is an optional part)
17. Service Port
18. Console Port
19. USB Port
20. Host Card Slot 2 (host card is an optional part)
21. Reset to Factory Default Button
22. Buzzer Mute Button

System Specification

Model Name	XS3312D	XS3312S
Architecture	Dual-active controller	Single-upgradable controller
CPU		
Processor	Intel® Xeon® 4-core x 2	Intel® Xeon® 4-core
Memory		
Memory Module Pre-installed	16 GB DDR4 RDIMM	8 GB DDR4 RDIMM
Total Memory Slots	8	4
Memory Expandable up to	512 GB	256 GB
Storage		
Drive Bays	3.5" Slot x 12	
Maximum Drive Bays with Expansion Unit	492	
Compatible Drive Type	3.5" & 2.5" SAS, NL-SAS, SED HDD 2.5" SAS, SED SSD	3.5" & 2.5" SAS, NL-SAS, SED HDD 3.5" & 2.5" SATA HDD 2.5" SAS, SATA, SED SSD
Drive Interface	SAS 12 Gb/s	SAS 12 Gb/s, SATA 6 Gb/s
Maximum Internal Raw Capacity	312 TB	
Maximum Raw Capacity with Expansion	12,792 TB	
Hot Swappable Drive	Yes	
Connectivity Port		
PCIe Expansion	(Gen 3x8 Slot) x 4	(Gen 3x8 Slot) x 2
1 GbE RJ45 LAN Port	2 (onboard)	1 (onboard)
10 GbE SFP+ LAN Port	8 (onboard) / 4 (option)	4 (onboard) / 4 (option)
10 GbE RJ45 LAN Port	2 (option) / 4 (option)	
25 GbE SFP28 LAN Port	2 (option) / 4 (option)	
16 Gb SFP+ Fibre Channel	2 (option) / 4 (option)	
32 Gb SFP28 Fibre Channel	2 (option) / 4 (option)	
Expansion and External Port		
12 Gb/s SAS Wide Port	4 (onboard)	2 (onboard)
USB Port	1 (front) / 2 (rear)	1 (front) / 1 (rear)
Others	Console Port x 2, Service Port x 2	Console Port x 1, Service Port x 1
Software Specification		
Storage OS	XEVO 2	
RAID Type	0 / 1 / 3 / 5 / 6 / 10 / 30 / 50 / 60 / 5EE / 6EE / 50EE / 60EE	
Storage Efficiency	Thin provisioning	
Software Acceleration	SSD cache (option) / Auto tiering (option)	
Data Protection	Snapshot / Asynchronous / Synchronous (option)	
Security	SSL / SSH / iSCSI CHAP / ISE & SED	
Support Protocols	iSCSI / FCP	
Management	Web UI / RESTful API / S.E.S. / LCM	
Appearance		
Dimension (H x W x D) (mm)	88 x 438 x 515	
Net Weight (kg)	16.4	
Gross Weight (kg)	18.8	
Others		
Memory Protection	Cache-to-Flash Module (Supercapacitor Module + Flash Module) (option)	
System Fan	4 pcs	
Power Supply Unit	850 W x 2 (80 Plus Platinum)	
Power Input	100 - 240 VAC, 50/60 Hz	
Power Consumption	407 W / 1,389 BTU	
Certification	CE / FCC / BSMI	
Standard Warranty	System: 3 years Supercapacitor Module: 1 year	

© 2025 QSAN Technology, Inc. All Rights Reserved. QSAN and the QSAN logo are registered trademarks of QSAN Technology, Inc. Other trademarks are the property of their respective companies. Product features, specifications, and appearance are subject to change without notice.

August 2025